

DHI-ART-ARC3000H-03-FW2

Dahua Wireless Alarm KIT



- Includes the following products: DHI-ARC3000H-FW2, DHI-ARD1233-W2, DHI-ARA24-W2 and DHI-ARD323-W2(S)
- Supports 150 wireless peripherals(6 sirens, 64 wireless keyfobs, 4 alarm repeaters, 8 wireless keypads, 8 PIR-Cameras);
- Peripherals status display (signal strength, battery level, temperature, program version);
- Wired, Wi-Fi, 4G, 3G or GPRS network connection;
- Dual SIM and Single Standby, auto switching;
- Automatic network replenishment (ANR);
- Video linkage on App;
- SOS emergency call;
- Frequency hopping function and two-way communication technology ensure communication stability;
- Cloud update and automatic recovery from update failure.

Series Overview

The Alarm Kit contains all the products required for a basic wireless alarm system, providing you and your assets with strong protection.

Technical Specification

Port

Wireless Zone	Hub: 150-channel wireless peripherals (6 sirens, 64 wireless keyfobs, 4 alarm repeaters, 8 wireless keypads, 8 PIR-Cameras)
Network Mode	Hub: Ethernet, Wi-Fi and Cellular network (Supports installation of dual SIM cards. Only one card can be enabled at a time)
Network Port	Hub: 1 × RJ-45 10 M/100 M Ethernet port
Storage Battery	Hub: Built-in lithium battery

Function

Indicator Light	Hub: 1 for multiple statuses (alarm, arming, disarming, networking, and malfunction) Keyfob: 1 × two-color status indicator (green: normal, red: abnormal) Door Detector: 1 × green alarm indicator PIR Detector: 1 × green alarm indicator
Button	Hub: 1 × reset, 1 × power, 1 × AP Keyfob: 4 (Home, Away, Disarm, and SOS) Door Detector: 1 × power button PIR Detector: 1 × power button
Buzzer	Hub: Built-in
SMS	Hub: Yes (up to 5 phone numbers)
Phone Call	Hub: Yes (up to 5 phone numbers)
Video Linkage	Hub: Yes
Offline Cache	Hub: Max. 50 entries (ANR)

Arm and Disarm	Hub: App; keyfob; schedule
Remote Update	All: Cloud update
Network Protocol	Hub: TCP/IP, including PPTP, L2TP, DHCP, UPNP, and NTP
Low Battery Detection	All: Yes
Tamper	Hub: Yes Door Detector: Yes PIR Detector: Yes
User Management	Hub: Share function for App users

Technical

Sensor	Door Detector: Reed switch PIR Detector: Dual elements low-noise PIR sensor
Detection Mode	PIR Detector: PIR
Sensitivity	PIR Detector: 3 levels adjustable
Detection Range	PIR Detector: 12 m (39.37 ft) (90°) with installation height of 2.2 m (7.21 ft)
Detection Speed	PIR Detector: 0.3 m/s–3 m/s (0.98 ft/s–9.84 ft/s)
Movement Distance	Door Detector: < 40 mm (1.57")
Pet Immunity Level	PIR Detector: ≤ 18 kg (39.68 lb)
White Light Resistance Level	PIR Detector: 2000 lx
Two-way Digital Temperature Compensation	PIR Detector: Yes, no attenuation of detection distance in high temperature

Alarm Kit | DHI-ART-ARC3000H-03-FW2

Test Mode	Door Detector: Yes PIR Detector: Yes
Scenario	Door Detector: Non-metal doors
Wireless	
Carrier Frequency	All: 433.1 MHz–434.6 MHz
Transmitter Power (EIRP)	All: Limit 10 mW
Communication Mechanism	All: Two-way
Communication Distance	Hub: Up to 1,200 m (3,937.01 ft) in an open space Keyfob: Up to 500 m (1,640.42 ft) in an open space Door Detector: Up to 1,000 m (3,280.84 ft) in an open space PIR Detector: Up to 1,200 m (3,937.01 ft) in an open space
Encryption Mode	All: AES128
Frequency Hopping	All: Yes
General	
Power Supply	Hub: 12 V DC, 1.5 A (USA power adapter) Keyfob: CR2032 battery Door Detector: CR123A battery PIR Detector: CR123A battery
Power Supply Type	Type A
Battery Life	Hub: Storage battery standby for 12 Hours Keyfob: 5 years Door Detector: 5 years PIR Detector: 4 years
Low Battery Threshold	2.7V
Battery Restore Threshold	2.8V
Power Consumption	Keyfob: ≤85 mW Door Detector: ≤70 mW PIR Detector: ≤75 mW
Operating Temperature	Hub: -10 °C to +50 °C (+14 °F to +122 °F) Keyfob: -10 °C to +55 °C (+14 °F to +131 °F) Door Detector: -10 °C to +55 °C (+14 °F to +131 °F) PIR Detector: -10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	All: 10%–90% (RH)
Product Dimensions	Hub: 163.0 mm × 163.0 mm × 32.0 mm (6.42" × 6.42" × 1.26") (L × W × H) Keyfob: 60.0 mm × 39.5 mm × 15.0 mm (2.36" × 1.56" × 0.59") (L × W × H) Door Detector: 100.2 mm × 20.8 mm × 20.3 mm (3.94" × 0.82" × 0.80") (L × W × H) PIR Detector: 104.0 mm × 60.0 mm × 50.0 mm (4.09" × 2.36" × 1.97") (L × W × H)
Net Weight	Hub: 380 g (0.84 lb) Keyfob: 20 g (0.04 lb) Door Detector: 70 g (0.15 lb) PIR Detector: 100 g (0.22 lb)
Gross Weight	880 g (1.94 lb)
Installation	Hub: Wall mount; Desktop Door Detector: Bracket mount PIR Detector: Wall mount
Casing Material	All: PC + ABS
Certifications	All: CE, FCC
Anti-corrosion Level	Basic Protection

Packaging Dimensions	265.0 mm × 238.0 mm × 76.0 mm (10.43" × 9.37" × 2.99") (L × W × H)
Wi-Fi	
Wi-Fi Standard	Hub: IEEE 802.11b/g/n
Wi-Fi Frequency Range	Hub: 2400–2483.5 MHz
Wi-Fi Power Transmission	Hub: ≤20 dBm@2400–2483.5 MHz
Cellular Network	
Cellular Network Standard	Hub: GSM/WCDMA/LTE
Frequency Range	Hub: LM: 4G: FDD-LTE: B1/B2/B3/B4/B5/B7/B8/B28; TDD-LTE: B40; 3G: WCDMA: B1/B2/B5/B8; 2G: GSM: 850/900/1800/1900 MHz;
Transmitter Power (EIRP)	Hub: 4G: Power class3: 23 dBm±2dB 3G: Power class3: 24 dBm+1/-3dB 2G: Power class0: 30 dBm±3dB (GSM900) Power class5: 33 dBm±3dB (GSM1800)

Ordering Information

Type	Model	Description
Alarm KIT	DHI-ART-ARC3000H-03-FW2	Dahua Wireless Alarm KIT

Application

